

## LL48 Linear LED Luminaires

### PRIMARY APPLICATIONS

Indoor and outdoor areas with low mounting heights or confined spaces, such as aisles, tunnels and catwalks, over doorways or entries, landing areas, utility rooms, etc.

### LUMINAIRE MODEL

Model Number	Equivalent HID Luminaire	Typical Energy Savings/Lifetime
LL48	2 x 58W fluorescent	Up to 50% reduction in energy costs and 60,000 hours of continuous operation!

### CERTIFICATIONS & COMPLIANCES

- Class I, Division 2, Groups A, B, C, D
- UL844; UL1598; UL1598A
- CSA C22.2 No. 137
- Type 4X, IP66

### ELECTRICAL RATINGS

- Voltage: 100-277 VAC

### OPTIONS AND ACCESSORIES

- Multiple mounting accessories, including: ceiling, wall, pole



Up to 50% more energy efficient than a 2x58W fluorescent light and 8 times the rated life

### DESIGN FEATURES

- A Versatile design** - Designed to match the footprint of a traditional linear fluorescent fixture.
- B Energy-efficient** - Same light pattern and lumen output at a fraction of the energy cost.
- C Better visibility** - Diffused lens reduces glare.
- D Shock- and vibration-resistant** - LEDs contain no mercury, eliminating costly lamp disposal programs.
- E Slim and low profile** - Designed for use in confined spaces.

